



LDV V80 3.5TON - DROPSIDE



Electric Side Mirrors
Electric and heated side mirrors with integrated turn signals; easy direction and placement control



Comfy Cabin
Three seater cabin. Driver seat with arm rest. Occupant safety is paramount to LDV, every LDV V80 comes with seatbelt pre-tensioning



Daytime running lights
Daytime running lights come as standard



Electric windows
The V80 is equipped with electric front windows with one touch control.



Cruise control
Activated at speeds above 60 kph in 4th gear or above. It is a very easy system to operate...



Bluetooth
Bluetooth is now fitted to the V80 allowing the hands-free use of mobile and music devices.



Air Conditioning
Manually operated air conditioning is a standard feature on the V80.



Door holders for large bottles
Easy convenient storage for large bottles located in the door for ease of use



FM/AM Sound system with MP3 Player
Standard entertainment system with Radio CD/MP3 and preset stations control



Dual Cup holders
Easy release dual cup holders as standard on all V80 Models

VEHICLE TYPE	BODY TYPE	WHEELBASE (mm)	CAB STYLE	CHASSIS LENGTH (REAR OVERHANG)mm.	BODY LENGTH : EXTERNAL (INTERNAL) mm.	BODY WIDTH : EXTERNAL (INTERNAL) mm.	CONVERTED VEHICLE KERB WEIGHT (MINIMUM KG SPEC) *	CALCULATED PAYLOAD (MINIMUM KG SPEC) ***
LDV V80 Chassis Cab	Dropside	3850	Single	Standard	3660 (3600) *	2090 (2030)	2005kg	1495kg
LDV V80 Chassis Cab	Dropside	3850	Single	Standard	3325 (3280) **	2090 (2030)	1975kg	1525kg

* for vehicles less Tail-lift and Towbar ** for vehicles with either Tail-lift or Towbar *** (minimum Spec) is LESS and optional content including Tail-lift

DIMENSIONS & WEIGHTS	
Length (mm)	5620
Front overhang (mm)	854
Rear overhang (mm)	916
Width excluding mirrors (mm)	1996
Width including mirrors (mm)	2383
Height (mm)	2136
Ground clearance (mm)	200
Wheel base (mm)	3850
Turning radius (m)	12.4
Gross vehicle mass (kg)	3500
Kerb weight (kg)	2375
Body & payload allowance (kg)	1725
Front axle capacity (kg)	1766
Rear axle capacity (kg)	2150
Gross Train Weight (GTW)	4000

MAXIMUM DIMENSIONS WITH BODY	
Maximum Length (mm)	6409
Maximum width (mm)	2100
Buildable cargo length (mm)	3890
Buildable overall width (mm)	2200

✓ Standard

Main Body is manufactured from Z140 Steel (Galvanised) and is a spot welded construction. Cab Protector (Front Bulkhead) is constructed from Z140 Steel (Galvanised) - Tested to 250kgs capacity loading.

All painted surfaces are phosphated and powder coated to a minimum of 80 microns.

Subject to Body Builder's specifications.

ENGINE / TRANSMISSION
VM Motori Eco-D2.5L turbo diesel engine with:
Bosch electronically controlled common rail direct fuel injection system
Turbo charger with inter-cooler
2499cc total displacement
100kW @ 3800rpm (136 PS)
330 Nm @ 1800 - 2600rpm
17.5:1 compression ratio
Six speed manual transmission

5 Year Warranty / 125,000 Miles (whichever comes first)

SAFETY FEATURES	
Anti-skid braking system (ABS)	✓
Electronic brake force distribution (EBD)	✓
Brake assist system (BAS)	✓
Driver and passenger airbags	✓
Side impact protect system (SIPS)	✓
Remote central locking	✓
Reverse parking sensor (four)	✓
Electronic stability programme (ESP)	✓
LED parking lights	✓



Luton / Box

2 rows of either load lock track or timber tie rail
Kick Strip all round
Non Slip Floor
LED interior light wired & switched to rear of body.

Curtainside Bodies

Kick Strip to bulkhead.
V Groove Aluminium side rave with pull up hooks to every 1000mm

Dropside Bodies

Standard aluminium lightweight headboard (re-inforced and braced, no mesh).
For Heavy Duty Steel Headboard - add 75kg
Single mill finish dropsides, rope hooks to every bearer.

Column Tail Lifts

DEL DL500G - 500kg Lift
Fit Free Issue Tail Lift:
815mm alloy platform, dual controls, fixed leading edge
Split folding/mesh platform dropsides

Roof Deflector

Supply & fit 3D Cab Deflector

Flush Doors

Supply & fit to curtainside / Low Frame Luton / Standard Luton

Barn Doors

Supply & fit to curtainside / Low Frame Luton / Standard Luton

